


## 3 Part Polyurethane Compound MDI

### 1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY:

PRODUCT NAME: 3 Part MDI Polyurethane Compound  
SUPPLIER: W T Henley Limited  
Silverkey, Church Manorway  
Belvedere Telephone: +44 (0) 1322 444500  
Kent DA8 1EX Facsimile: +44 (0) 1322 444502

### 2. COMPOSITION/INFORMATION ON INGREDIENTS:

Labelled Components

INGREDIENTS	CAS No	%(w/w)	Symbol	Hazard Code
4,4 Diphenylmethane Diisocyanate Isomers and homologues	9016-87-9	<25	 Warning	H315, H317, H319, H332, H334, H335, H351, H373

### 3. HAZARDS IDENTIFICATION:

Main Health Hazards Harmful By inhalation  
Irritating to eyes, respiratory system and skin  
May cause sensitisation by inhalation  
Suspected of causing cancer category 2

### 4. FIRST AID MEASURES:

INHALATION: Remove to fresh air, keep warm and if recovery is not rapid, seek medical attention

SKIN CONTACT: Remove contaminated clothing and wash with plenty of soap and water. Do not use organic solvents

EYE CONTACT: Immediate and continual flushing of the eye is essential, Seek Medical attention

INGESTION: If large amounts are ingested wash out mouth with clean cold water and seek medical attention.

**5. FIRE FIGHTING MEASURES:**

## SUITABLE EXTINGUISHING

MEDIA: C02, Water Spray or Foam.

## HAZARDS

Combustion Products include water; oxides of carbon and nitrogen, traces of hydrogen cyanide may also be evolved.

## REQUIRE SPECIAL PROTECTIVE EQUIPMENT

FOR FIRE FIGHTERS: In enclosed spaces wear self-contained breathing apparatus and full protective clothing

**6. ACCIDENTAL RELEASE MEASURES:**

PERSONAL PRECAUTIONS: Do not breathe vapour, avoid ignition sources, and avoid contact with skin, eyes or clothing.

ENVIRONMENTAL  
PRECAUTIONS:

Prevent contamination of soil, drains and surface water.

WORKPLACE  
PRECAUTIONS

Ensure personnel are wearing suitable protective equipment.

## METHOD OF CLEANING:

Absorb into damp sand or equivalent and place in suitable closed container for disposal in accordance with local and national regulations

**7. HANDLING AND STORAGE:**

7.1 HANDLING: Wear plastic gloves

7.2 STORAGE: Recommended storage temperature between +10 deg. C and +25deg. C.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION:**

No special precautions are necessary, although sensible industrial clothing is recommended.

EXPOSURE CONTROL LIMITS: Isocyanate 0.02 mg.m<sup>-3</sup> 8 hour TWA  
Silica Sand 0.08 mg. m<sup>-3</sup> 8 hour TWA

RESPIRATORY PROTECTION: Wear dust mask if large amounts of dust are generated

HAND PROTECTION: Wear plastic gloves

EYE PROTECTION: Wear safety glasses

SKIN PROTECTION: Wear sensible industrial clothing, wash regularly.

**9. PHYSICAL AND CHEMICAL PROPERTIES:**

	BASE	HARDENER	SECONDARY FILLER
APPEARANCE:	Buff Liquid	Brown Liquid	Granular solid
ODOUR:	Typical of a natural vegetable oil	Musty	None
pH:	Not applicable	Not applicable	Not applicable
BOILING POINT RANGE:	Above 300 deg. C	Above 300 deg.C	Not applicable
MELTING POINT RANGE:	Not applicable	Not applicable	Not applicable
FLASH POINT:	Above 200 deg. C (open cup)	Above 200 deg. C (open cup)	Not applicable
FLAMMABILITY:	Not flammable at normal temperatures	Not flammable at normal temperatures	Not applicable
AUTO-FLAMMABILITY:	May auto-ignite above 300 deg C	May auto-ignite over 300 deg C	Not applicable
EXPLOSIVE PROPERTIES:	Not applicable	Not applicable	Not applicable
OXIDISING PROPERTIES:	Not applicable	Not applicable	Not applicable
VAPOUR PRESSURE:	<10 mbar @20C	<0.00001 mbar @20C	Not applicable
RELATIVE DENSITY:	1.4	1.24	2.65
SOLUBILITY IN Water:	Insoluble	Insoluble	Insoluble

**10. STABILITY AND REACTIVITY:**

CONDITIONS TO AVOID: None

MATERIALS TO AVOID: Strong alkalis and acids

**HAZARDOUS DECOMPOSITION**

PRODUCT (S): None when stored and used correctly. At temperatures in excess of 200 C decomposition products may include oxides of nitrogen and carbon.

**11. TOXICOLOGICAL INFORMATION:**

	Base	Hardener	Secondary filler
EYE CONTACT:	Possible Irritation	Irritation	Irritation
SKIN EFFECT:	Possible irritation	Possible irritation and sensitisation	Possible irritation
INHALATION:	Irritation unlikely	possible irritation and sensitisation	Possible irritation
INGESTION:	Possible Purgative	Possible gastric Irritation	Possible gastric irritation
EXPOSURE LIMITS		0.02 mg per cubic metre, 8 ht TWA 0.07 mg per cubic metre, 15 min STEL	0.08 mg per cubic metre 8hr TWA

---

**12. ECOLOGICAL INFORMATION:**

---

Do not allow liquid components to escape into soil watercourses or drains

---

**13. DISPOSAL CONSIDERATIONS:**

---

Disposal should be in accordance with local, state or national legislation.

---

**14. TRANSPORT INFORMATION:**

---

Not classified as dangerous for transport

---

**15. OTHER INFORMATION:**

---

Date of preparation      February 2011

Liability: such information is to the best of WT Henley Limited's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made to its accuracy, reliability or completeness. It is the users responsibility to satisfy itself as to its suitability and completeness of such information for their own particular use.

---

The data contained in this safety data sheet has been supplied as required by the **Chemicals (Hazard Identification and Packaging for Supply) Regulations 1994** for the purpose of protecting health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided.

**Please ensure that it is passed unto the appropriate person(s) in your company, who are capable of acting on the information.**