


Fused Multi Service Pillars

Rated 240/415V



W T Henley is a world leader in the design and manufacture of Electrical Distribution Equipment.

Providing a safe, and reliable low voltage supply to rural dwellings is easy, with our choice of Multi Service Pillar designs.

Ideal for Caravan sites, Holiday Chalets, small groups of houses and market areas, they allow a simple means of protection and isolation.

Central to the design are our well established range of Series 7 House Service Cut-outs, which can be fused from 100A downwards

The design incorporates a lift-off GRP cover, which is largely unobtrusive in rural areas.

We have a choice of two designs:

- 1) 4-way triple-pole-and-neutral (12-way single-pole-and-neutral)
- 2) 6-way triple-pole-and-neutral (18-way single-pole-and-neutral)

Service fuses are mounted in three single-phase banks with a multi-way neutral connector block below and accept up to 35mm² copper or aluminium conductors.

- **Reliable and safe method of supply/isolation.**
- **Simple design and easily installed.**
- **Suits CNE or SNE type cables.**
- **Tough 'easilift' GRP cover, unobtrusive in rural areas.**
- **Choose between 60/80 or 100A rating, using our own ESI approved Series 7 Cut-outs.**
- **Tough concrete root/plinth minimises corrosion problems at ground level.**



A subsidiary of TT electronics plc



WT Henley Limited



Pillar Selection Chart

58134-16	4-way	Triple-pole-and-neutral unit (excluding carriers)
58134-88	6-way	Triple-pole-and-neutral unit (excluding carriers)
54365-04	60/80A	Fuse Carriers (excluding fuselinks)
54365-22	100A	Fuse Carriers (excluding fuselinks)

Please note: When selecting fuse carriers 12 are required for a 4-way unit
18 are required for a 6-way unit.

Dimensions in mm

Detail	4-way	6-way
Overall height above ground	920	920
Height of GRP cover only	640	640
Concrete base	280	280
Nominal depth of concrete in ground	380	380
Total height including root section	1300	1300
Maximum width of Pillar	358	461
Maximum depth of Pillar	334	334
Fixing centres of root	378	378

Approximate Gross Weight (inc root) kg

4-way	91
6-way	113



Note:

- A) Owing to space limitations on the gland plates, the full number of outgoing SP/N services i.e. 12 or 18 cannot be accommodated if terminating glands are to be fitted for armoured service cables. Further information is available on request.
- B) Fuselinks to BS 1361 Type II required for Series 7 fuse units.

WT Henley Limited

Silver Key, Church Manorway
Belvedere, Erith, Kent DA8 1EX, England

Telephone: +44 (0) 1322 444500
Facsimile: +44 (0) 1322 444502
Email: sales@wt-henley.com

Website: www.wt-henley.com



General Note The equipment detailed in this publication should be installed by a suitably qualified person. WT Henley Limited reserves the right to make changes in product specification without notice or liability. All information is subject to WT Henley's own data and is considered accurate at time of going to print.

© 2002 WT Henley Limited. All rights reserved. No part of this document may be copied or reproduced in whole or in part without prior written approval of WT Henley Limited.

A subsidiary of TT electronics plc